

DECLARATION OF PERFORMANCE

No. 64633-a-CPR_2018.10.1

Unique identification code of the product-type	Du.Panel X
Intended use/es	Thermal insulation for buildings
Manufacturer	Recticel NV - Zuidstraat 15 - B-8560 Wevelgem
System/s of AVCP	AVCP 1 & AVCP 3
Harmonised standard	EN 13165:2012 + A2:2016
Notified body/ies	Notified certification body No. NB 0751 performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of constancy of performance for reaction to fire under system AVCP 1. Notified testing laboratory No. NB 0751 & NB 1173 determined the production type under system AVCP3.

Essential characteristics	Performance	
	(The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)	
Reaction to fire	Reaction to fire	B-S2-d0
Thermal resistance	Thermal resistance (R_D in m^2K/W)	2,00 for d_N 40mm 6,00 for d_N 120mm
	Thermal conductivity (λ_D in W/mK)	0,020
Thickness	d_N : 40-120 mm	T2
Compressive strength	CS(10/Y)150	
Tensile strength/shear behaviour	Tensile strength perpendicular to faces:	TR80
	Shear strength:	NPD
	Shear modulus:	NPD
Water permeability	Water absorption	NPD
	- short term by partial immersion	NPD
	- long term by partial immersion	WL(T)2
	- long term by total immersion	NPD
Flatness after one-sided wetting	NPD	
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Direct airborne sound insulation index	Sound absorption	NPD
Continuous glowing combustion	No harmonized test method available	
Release of dangerous substances to the indoor environment	No harmonized test method available	
Durability of reaction to fire against heat, weathering, ageing / degradation	Reaction to fire does not change with time	
Dimensional stability under specified temperature and humidity conditions	48h, 70°C, 90% R.H.	DS(70,90)3
	48h, -20°C	DS(-20,-)1
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	NPD
Compressive creep		NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

at Wevelgem on October 1st 2018

Wim Giebens – Industrial Manager Recticel Building Insulation

Wim Giebens – Industrial Manager Recticel Building Insulation

