



Panels of agglomerated polyurethane foam and fibres to improve the transmission sound insulation of interiors walls of homes.

Application(s)

Instasoft® is a product designed to improve internal sound and thermal insulation (internal side of external walls) ; it may be applied to a separation wall between two apartments (in the same building), as well as to the inside of an exterior wall perimeter and a separation wall of a house. *

Board

Description	Standards	Value	Unit
Dimensions			
Length	EN 822	1200	mm
Width	EN 822	600	mm
Thickness range	EN 823	40	mm
Density (core volume weight)	EN 1602	80	kg/m³
Appearance**			
Appearance of surface	Respects a flat surface - Agglomerated foam		
Edge finishing	Straight-line cut, square edges - Agglomerated foam		
* Instasoft® must always be covered with at least a 12.5 mm thick plasterboard in order to meet fire safety requirements.			
** Product manufactured from recycled materials. The composition and visual appearance may vary, but this will not affect performance.			
The plasterboard joints should have a sufficient offset in relation to the Instasoft® joints.			

Care has been taken to ensure that the content of this document is as accurate as possible. Please note that technical specifications may vary from country to country. Recticel Insulation does not accept any liability for clerical errors and reserves the right to amend information without prior notice. This document does not create, specify, modify or replace any new or prior contractual obligations agreed upon in writing between Recticel Insulation and the user.

Recticel Insulation

Zuidstraat 15, 8560 Wevelgem, Belgium

www.recticelinsulation.com

FEEL
GOOD
INSIDE

RECTICEL
insulation

Essential characteristics

Description	Standards	EN code	Value	Unit
Thermal conductivity (declared value)	EN 12667	λ_D	0,037	W/m.K
Thermal resistance	EN 12667	RD	1.05	m²K/W
Sound properties				
Airborne sound insulation (1)	Classified according to EN ISO 717-1:2013 Tested according to EN ISO 10140-2:2010 and EN ISO 10140-5:2010+A1:2014	ΔR_w	9	dB
Mechanical properties				
Tensile strength perpendicular to faces	EN 1607	TR40	≥ 40	kPa
Fire behaviour				
Reaction to fire (end use) (covered with a plasterboard of 12.5 mm)	EN 13501-1	Euroclass	B-s1,d0	
Reaction to fire (product as such) (Instasoft® only)			NPD	

Standards & Certificates

Standards

Production	ISO 9001 : 2015
European assessment document (EAD)	040831-01-1201

Certificates

ETA	20/0396
VOC (2)	A+

Other / Miscellaneous

Production

Recticel SAS ZI-7 Boulevard de la Chanterie-49124 Saint Barthélemy d'Anjou-France

Storage/handling Stock dry and protected from direct sunlight

(1) Sound test report reference AC7443-F of Simfofit® (same composition and characteristics as Instasoft®).

(2) Test report reference N° D-231216-10619 of Simfofit® (same composition and characteristics as Instasoft®).

Remark: Instasoft® is not suitable as floor or ceiling insulation, also use in wet rooms e.g. bathroom is prohibited.

Care has been taken to ensure that the content of this document is as accurate as possible. Please note that technical specifications may vary from country to country. Recticel Insulation does not accept any liability for clerical errors and reserves the right to amend information without prior notice. This document does not create, specify, modify or replace any new or prior contractual obligations agreed upon in writing between Recticel Insulation and the user.

Recticel Insulation

Zuidstraat 15, 8560 Wevelgem, Belgium

www.recticelinsulation.com

FEEL
GOOD
INSIDE

RECTICEL
insulation