

LISTE DE CONDITIONNEMENT

TYPE	EPAISSEURS	DIMENSIONS	NOMBRE/PQT	M ² /PQT	M ³ /PQT
EUROWALL®	30 mm	600 x 1200 mm	16	11,52	0,35
	40 mm		12	8,64	0,35
	50 mm		10	7,20	0,36
	60 mm		8	5,76	0,35
	70 mm		7	5,04	0,35
	82 mm		6	4,32	0,35
	95 mm		5	3,60	0,34
	100 mm		5	3,60	0,36
	110 mm		4	2,88	0,32
	120 mm		4	2,88	0,35
	130 mm*		3	2,16	0,28
	140 mm		3	2,16	0,30
	150 mm*		3	2,16	0,32
	160 mm		3	2,16	0,35
EUROWALL® 21	60 mm	600 x 1200 mm	8	5,76	0,35
	75 mm		6	4,32	0,32
	90 mm		5	3,60	0,32
	100 mm		5	3,60	0,36
	120 mm*		4	2,88	0,35
EUROFLOOR	20 mm	1200 x 2500 mm	9	27,00	0,54
	30 mm		12	36,00	1,08
	40 mm		9	27,00	1,08
	50 mm		7	21,00	1,05
	60 mm		6	18,00	1,08
	70 mm		5	15,00	1,05
	80 mm		4	12,00	0,96
	90 mm*		4	12,00	1,08
	100 mm		3	9,00	0,90
	EURO-FLOOR 300		60 mm	600 x 1200 mm	8
80 mm		6	4,32		0,35
100 mm		5	3,60		0,36
EUROTHANE® G 10 + ...	20 mm	1200 x 2600 mm	40	124,80	2,50
	30 mm		30	93,60	2,81
	40 mm		24	74,88	3,00
	50 mm		20	62,40	3,12
	60 mm		17	53,04	3,18
	80 mm		13	40,56	3,24
	100 mm		10	31,20	3,12
	120 mm*		9	28,08	3,37
EUROTHANE® G ÉPAISSEUR 600 mm 10 + ...	20 mm*	600 x 2600 mm	80	124,80	2,50
	30 mm*		60	93,60	2,81
	40 mm*		48	74,88	3,00
	50 mm*		40	62,40	3,12
	60 mm*		34	53,04	3,18
	80 mm*		26	40,56	3,24
	100 mm*		20	31,20	3,12

* niet op voorraad

LISTE DE CONDITIONNEMENT

TYPE	EPAISSEURS	DIMENSIONS	NOMBRE/PQT	M ² /PQT	M ³ /PQT
EUROTHANE® BI-4	30 mm	600 x 1200 mm	16	11,52	0,35
	40 mm		12	8,64	0,35
	50 mm		10	7,20	0,36
	60 mm		8	5,76	0,35
	70 mm		7	5,04	0,35
	80 mm		6	4,32	0,35
	91 mm*		5	3,60	0,32
	100 mm		5	3,60	0,36
	120 mm		4	2,88	0,35
	140 mm		3	2,16	0,40
	160 mm*	3	2,16	0,35	
EUROTHANE® BI-4A POWERDECK® F A	20/40	600 x 1200 mm	12	8,64	0,26
	40/60		8	5,76	0,29
	60/80		6	4,32	0,30
	80/100		4	2,88	0,26
EUROTHANE® BI-4A POWERDECK® F A	30/45	600 x 1200 mm	10	7,20	0,27
	45/60		8	5,76	0,31
	60/75		6	4,32	0,29
	75/90		4	2,88	0,24
	90/105		4	2,88	0,28
EUROTHANE® SILVER	30 mm	600 x 1200 mm	16	11,52	0,35
	40 mm		12	8,64	0,35
	50 mm		10	7,20	0,36
	60 mm		8	5,76	0,35
	70 mm		7	5,04	0,35
	81 mm		6	4,32	0,35
	90 mm		5	3,60	0,32
	100 mm		5	3,60	0,36
	110 mm		4	2,88	0,32
	120 mm		4	2,88	0,35
	130 mm		3	2,16	0,28
	140 mm		3	2,16	0,30
	150 mm*		3	2,16	0,32
160 mm*	3	2,16	0,35		
EUROTHANE® SILVER	30 mm	1200 x 2500 mm	12	36,00	1,08
	40 mm		9	27,00	1,08
	50 mm		7	21,00	1,05
	60 mm		6	18,00	1,08
	70 mm		5	15,00	1,05
	81 mm		4	12,00	0,97
	90 mm		4	12,00	1,08
	100 mm		3	9,00	0,90
	110 mm		3	9,00	0,99
	120 mm		3	9,00	1,08
	130 mm*		3	9,00	1,17
	140 mm		3	9,00	1,26
	150 mm*		3	9,00	1,35
160 mm*	2	6,00	1,44		

* sur demande

LISTE DE CONDITIONNEMENT

TYPE	EPAISSEURS	DIMENSIONS	NOMBRE/PQT	M ² /PQT	M ³ /PQT
POWERDECK®	30 mm*	1200 x 2500 mm	12	36,00	1,08
	40 mm*		9	27,00	1,08
	50 mm*		7	21,00	1,05
	60 mm*		6	18,00	1,08
	70 mm*		5	15,00	1,05
	80 mm*		4	12,00	0,96
	90 mm*		4	12,00	1,08
	100 mm*		3	9,00	0,90
	110 mm*		3	9,00	0,99
	120 mm*		3	3,60	0,43
	140 mm*	3	2,16	0,30	
POWERDECK® F	30 mm	600 x 1200 mm	16	11,52	0,35
	40 mm		12	8,64	0,35
	50 mm		10	7,20	0,36
	60 mm		8	5,76	0,35
	70 mm		7	5,04	0,35
	80 mm		6	4,32	0,35
	91 mm		5	3,60	0,33
	100 mm		5	3,60	0,36
	110 mm*		4	2,88	0,32
	120 mm		4	2,88	0,35
	140 mm		3	2,16	0,30
	160 mm*		3	2,16	0,35
	180 mm*		2	1,44	0,26
POWERDECK® F	30 mm*	1200 x 2500 mm	8	24,00	0,72
	40 mm*		12	36,00	1,44
	50 mm*		10	30,00	1,50
	60 mm		8	24,00	1,44
	70 mm*		6	18,00	1,26
	80 mm		6	18,00	1,44
	91 mm*		5	15,00	1,37
	100 mm		3	9,00	0,90
	110 mm*		3	9,00	0,99
	120 mm		3	9,00	1,08
	140 mm*		3	9,00	1,26
	160 mm*		3	9,00	1,44
	180 mm*		2	6,00	1,08
POWERROOF® POWERROOF® MAX	60 mm*	1200 x 2500 mm	6	18,00	1,08
	80 mm		4	12,00	0,96
	90 mm*		4	12,00	1,08
	100 mm		3	9,00	0,90
	120 mm		3	9,00	1,08
	140 mm		3	9,00	1,26
	160 mm		2	6,00	0,96
	180 mm		2	6,00	1,08
POWERWALL®	40 mm*	600 x 1200 mm	12	8,64	0,35
	50 mm*		10	7,20	0,36
	60 mm		8	5,76	0,35
	70 mm*		7	5,04	0,35
	80 mm		6	4,32	0,35
	90 mm		5	3,60	0,32
	100 mm		5	3,60	0,36
	120 mm		4	2,88	0,35

* sur demande

FEEL
GOOD
INSIDE

RECTICEL
insulation

01-2019