# Declaration of performance

# No. 64238-a-CPR_2026.10.1

EN

| | | |
|---|---|---|
| 1. | Unique identification code of the product-type | **64238 – PU Rigid board gastight facing adhered to a tapered edge standard wallboard** |
| 2. | Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4) | **See CE mark label and marking on boards** |
| 3. | Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer | **Gypsum plasterboard composite panel for internal use in buildings** |
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5) | **Eurothane PL<br>Recticel Ltd.<br>Enterprise Way, Meir Park<br>Stoke-on-Trent, ST3 7UN<br>UK** |
| 5. | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2) | **Not relevant** |
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V | **System 4 generally<br>System 3 for Reaction to Fire** |
| 7. | In case of the declaration of performance concerning a construction product covered by a harmonised standard | **EN 13950:2014<br>The Building Test Centre, Approved body No. 0832 issued reports relating to System 3 classification for reaction to fire** |
| 8. | In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued | **Not relevant** |

9. **Declared performance**

| **Essential characteristics** | **Performance** (The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.) | **Harmonised technical specification** |
|---|---|---|
| Shear strength | NPD | N/A |
| Reaction to fire | B-s1, d0 | EN 13950:2014 |
| Water vapour resistance factor | 845 | EN 13950:2014 |
| Impact resistance | NPD | NPD |
| Direct airborne sound insulation | NPD | NPD |
| Acoustic absorption | NPD | N/A |
| Longitudinal flexural strength | 400 N | EN 13950:2014 |
| Transverse flexural strength | 160 N | EN 13950:2014 |
| Thermal resistance | Thickness 37,5mm: 1,15 m².K/W | EN 13950:2014 |
| | Thickness 132,5mm: 5,50 m².K/W | |

Where pursuant to Article 37 or 38, the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not relevant**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
Signed for and on behalf of the manufacturer by:
Wevelgem on October 22nd 2026

Kurt Verhooghe – Operations Director Recticel Insulation Boards



recticel